Index to

EXPERIMENTAL MECHANICS

Volume 44, 2004

TITLE INDEX

A Device for Measuring the Velocity of Ultrasonic Waves: An Application to Stress Analysis, 44(1), M. Sgalla and D. Vangi, 85–90.

A Method for Measuring Mode I Crack Tip Constraint Under Static and Dynamic Loading Conditions, 44(5), M.J. Maleski, M.S. Kirugulige and H.V. Tippur, 522–532.

A New Hybrid Technique for In-plane Characterization of Orthotropic Materials, 44(6) K. Genovese, L. Lamberti and C. Pappalettere, and 584–592.

A Novel Specimen for Investigating the Mechanical Behavior of Elastomers Under Multiaxial Loading Conditions, 44(2), W.V. Mars and A. Fatemi, 136–146.

A Piezoelectric Biaxial Loading Device for Interfacial Fracture Experiments, 44(5), A.W. Mello, and K.M. Liechti, 495–501.

A Procedure for Measuring Biaxial Viscoelastic Behavior of Thermoplastics, 44(4), S.R. Hummel and H.F. Nied, 381–386.

A Rigorous Assessment of the Benefits of Miniaturization in the Kolsky Bar System, 44(5), D. Jia and K.T. Ramesh, 445–454.

Advances in Light Microscope Stereo Vision, 44(3), H. Schreier, D. Garcia and M.A. Sutton, 278–288.

An Empirical Methodology to Estimate a Local Yield Stress in Workhardened Surface Layers, 44(1), J.P. Nobre, A.M. Dias and Dr. M. Kornmeier, 76–84.

An Experimental-Numerical Evaluation of the T_{ξ}^{*} Integral for a Three-dimensional Crack Front, 44(2), John H. Jackson, A.S. Kobayashi and S.N. Atluri, 207–213.

Analytical/Experimental Investigation of Energy Absorption in Grid-stiffened Composite Structures Under Transverse Loading, 44(2), C. Gan, R.F. Gibson and G.M. Newaz, 185–194.

Ball Spin Generation for Oblique Impacts with a Tennis Racket, 44(2), S.R. Goodwill, and S.J. Haake, 195–206.

Behavior of a Small Single Bubble Rising in a Rotating Flow Field, 44(5), T. Yamaguchi, M. Iguchi and T. Uemura, 533–540.

Bending Actuation in Polyurethanes with a Symmetrically Graded Distribution of One-way Shape Memory Alloy Wires, 44(1), H. Bruck, C.L. Moore, III and T.M. Valentine, 62–70.

Combined Shear/Compression Structural Testing of Asymmetric Sandwich Structures, 44(5), B. Castanie, J.J. Barrau, J.P. Jaouen and S. Rivallant, 461–472.

Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), R.L. Edwards, G. Coles and W.N. Sharpe, Jr., 49–54.

Crack Instability in Ductile Materials Analyzed by the Method of Interpolated Ellipses, 44(4), D. Vavrik and J. Zemankova, 327–335.

Crushability Maps for Structural Polymeric Foams in Uniaxial Loading Under Rigid Confinement, 44(3), G. Subhash and Q. Liu, 289–294.

Design and Evaluation of the Poleidoscope: A Novel Digital Polariscope, 44(2), J. Lesniak, S.J. Zhang and E.A. Patterson, 128–135.

Determination of the Optimal Gabor Wavelet Shape for the Best Time-Frequency Localization Using the Entropy Concept, 44(4), J.-C. Hong and Y.Y. Kim, 387–395.

Determining Stress Intensity Factors in Orthotropic Composites From Far-field Measured Temperatures, 44(6) K.Y. He and R.E. Rowlands, 555–561.

Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part I: A Biologically Inspired Design, 44(6) L.R. Xu, H. Kuai and S. Sengupta, 608–615.

Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part II: An Integrated Numerical Analysis, 44(6) L.R. Xu and S. Sengupta, 616–621.

Dynamic Compressive Responses of Intact and Damaged Ceramics from a Single Split Hopkinson Pressure Bar Experiment, 44(3), W.W. Chen and H. Luo, 295–299.

Dynamic Crack Kinking from a PMMA/Homalite Interface, 44(2), J. Kimberley and J. Lambros, 158–166.

Dynamic Force-Penetration Curves in Rock by Matching Theoretical to Experimental Wave Propagation Response, 44(2), L.E. Chiang, 167–175.

Dynamic Stress Equilibration in Split Hopkinson Pressure Bar Tests on Soft Materials, 44(3), B. Song and W. Chen, 300–312.

Editorial, 44(6) Nancy R. Sottos, 543.

Effect of Strain Rate, Moisture and Temperature on the Deformation Behavior of Polymer Roll Covers, 44(3), T. Vuoristo and V.-T. Kuokkala, 313–319.

Effects of Measurement Techniques on the Experimental Characterization of Crack Tip Opening Angle-Δa Resistance Curves, 44(4), W. Burton, S. Mahmoud and K. Lease, 425–432.

Erratum to Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(5), M.B. Prime, 541–541.

Estimating Deflection of a Simple Beam Model Using Fiber Optic Bragg-grating Sensors, 44(4), N.-S. Kim and N.-S. Cho, 433–439.

Experimental Estimation of the Load Distribution in Bearings by the Method of Caustics, 44(4), G.A., Papadopoulos, 440–443.

Experimental Evaluation of the Wyoming-modified Two-rail Shear Test Method for Composite Materials, 44(4), A.K. Hussian and D.F. Adams, 354–364.

Experimental Modal Analysis of a Synthetic Composite Femur, 44(1), J.F. Dias Rodridgues, H. Lopes, F.Q. de Melo and J.A. Simões, 29–32.

Experimental Studies on Thin-walled Grooved Tubes Under Axial Compression, 44(1), S.J. Hosseinipour and G.H. Daneshi, 101–108.

Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), B.D. Johnson, D.J. Beebe, D.J. Niedermaier, J.M. Bauer and W.C. Crone, 21–28.

Experimental Techniques For Testing Unstiffened Plates in Compression and Bending, 44(1), M.R. Bambach and K.J.R. Rasmussen, 91–96.

Experimental Verification of Drop/Impact Simulation for a Cellular Phone, 44(4), J.G. Kim and Y.K. Park, 375–380.

Failure Loads of Spot Weld Specimens Under Impact Opening and Shear Loading Conditions, 44(2), S.H. Lin, J. Pan, S. Wu and T. Tyan, 147–157.

Fatigue Cracking and Its Influence on Dynamic Response Characteristics of Spot Welded Specimens, 44(5), G. Wang and M.E. Barkey, 512–521.

Fatigue Damage Accumulation Around a Notch Using a Digital Image Measurement System, 44(3), F.V. Diaz, A.F. Armas, G.H. Kaufmann and G.E. Galizzi, 241–246.

Grid Method: Application to the Characterization of Cracks, 44(1), S. Avril, A. Vautrin and Y. Surrel, 37–43.

Impedance-based Non-destructive and Non-parametric Infrastructural Performance Evaluation, 44(1), K.K. Tseng, 109–112.

Improved Experimental Tracking Techniques for Validating DEM Simulations of Tumbling Mills, 44(6), I. Govender, A.T. McBride and M. S. Powell, 593–607.

Innovative Mechanical Device for the Post-tensioning of Glass Fiber Reinforced Polymer Bars for Masonry Type Retrofit Applications, 44(3), P. Yu, P.F. Silva and A. Nanni, 272–277.

Index to

EXPERIMENTAL MECHANICS

Volume 44, 2004

TITLE INDEX

A Device for Measuring the Velocity of Ultrasonic Waves: An Application to Stress Analysis, 44(1), M. Sgalla and D. Vangi, 85–90.

A Method for Measuring Mode I Crack Tip Constraint Under Static and Dynamic Loading Conditions, 44(5), M.J. Maleski, M.S. Kirugulige and H.V. Tippur, 522–532.

A New Hybrid Technique for In-plane Characterization of Orthotropic Materials, 44(6) K. Genovese, L. Lamberti and C. Pappalettere, and 584–592.

A Novel Specimen for Investigating the Mechanical Behavior of Elastomers Under Multiaxial Loading Conditions, 44(2), W.V. Mars and A. Fatemi, 136–146.

A Piezoelectric Biaxial Loading Device for Interfacial Fracture Experiments, 44(5), A.W. Mello, and K.M. Liechti, 495–501.

A Procedure for Measuring Biaxial Viscoelastic Behavior of Thermoplastics, 44(4), S.R. Hummel and H.F. Nied, 381–386.

A Rigorous Assessment of the Benefits of Miniaturization in the Kolsky Bar System, 44(5), D. Jia and K.T. Ramesh, 445–454.

Advances in Light Microscope Stereo Vision, 44(3), H. Schreier, D. Garcia and M.A. Sutton, 278–288.

An Empirical Methodology to Estimate a Local Yield Stress in Workhardened Surface Layers, 44(1), J.P. Nobre, A.M. Dias and Dr. M. Kornmeier, 76–84.

An Experimental-Numerical Evaluation of the T_{ξ}^{*} Integral for a Three-dimensional Crack Front, 44(2), John H. Jackson, A.S. Kobayashi and S.N. Atluri, 207–213.

Analytical/Experimental Investigation of Energy Absorption in Grid-stiffened Composite Structures Under Transverse Loading, 44(2), C. Gan, R.F. Gibson and G.M. Newaz, 185–194.

Ball Spin Generation for Oblique Impacts with a Tennis Racket, 44(2), S.R. Goodwill, and S.J. Haake, 195–206.

Behavior of a Small Single Bubble Rising in a Rotating Flow Field, 44(5), T. Yamaguchi, M. Iguchi and T. Uemura, 533–540.

Bending Actuation in Polyurethanes with a Symmetrically Graded Distribution of One-way Shape Memory Alloy Wires, 44(1), H. Bruck, C.L. Moore, III and T.M. Valentine, 62–70.

Combined Shear/Compression Structural Testing of Asymmetric Sandwich Structures, 44(5), B. Castanie, J.J. Barrau, J.P. Jaouen and S. Rivallant, 461–472.

Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), R.L. Edwards, G. Coles and W.N. Sharpe, Jr., 49–54.

Crack Instability in Ductile Materials Analyzed by the Method of Interpolated Ellipses, 44(4), D. Vavrik and J. Zemankova, 327–335.

Crushability Maps for Structural Polymeric Foams in Uniaxial Loading Under Rigid Confinement, 44(3), G. Subhash and Q. Liu, 289–294.

Design and Evaluation of the Poleidoscope: A Novel Digital Polariscope, 44(2), J. Lesniak, S.J. Zhang and E.A. Patterson, 128–135.

Determination of the Optimal Gabor Wavelet Shape for the Best Time-Frequency Localization Using the Entropy Concept, 44(4), J.-C. Hong and Y.Y. Kim, 387–395.

Determining Stress Intensity Factors in Orthotropic Composites From Far-field Measured Temperatures, 44(6) K.Y. He and R.E. Rowlands, 555–561.

Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part I: A Biologically Inspired Design, 44(6) L.R. Xu, H. Kuai and S. Sengupta, 608–615.

Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part II: An Integrated Numerical Analysis, 44(6) L.R. Xu and S. Sengupta, 616–621.

Dynamic Compressive Responses of Intact and Damaged Ceramics from a Single Split Hopkinson Pressure Bar Experiment, 44(3), W.W. Chen and H. Luo, 295–299.

Dynamic Crack Kinking from a PMMA/Homalite Interface, 44(2), J. Kimberley and J. Lambros, 158–166.

Dynamic Force-Penetration Curves in Rock by Matching Theoretical to Experimental Wave Propagation Response, 44(2), L.E. Chiang, 167–175.

Dynamic Stress Equilibration in Split Hopkinson Pressure Bar Tests on Soft Materials, 44(3), B. Song and W. Chen, 300–312.

Editorial, 44(6) Nancy R. Sottos, 543.

Effect of Strain Rate, Moisture and Temperature on the Deformation Behavior of Polymer Roll Covers, 44(3), T. Vuoristo and V.-T. Kuokkala, 313–319.

Effects of Measurement Techniques on the Experimental Characterization of Crack Tip Opening Angle-Δa Resistance Curves, 44(4), W. Burton, S. Mahmoud and K. Lease, 425–432.

Erratum to Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(5), M.B. Prime, 541–541.

Estimating Deflection of a Simple Beam Model Using Fiber Optic Bragg-grating Sensors, 44(4), N.-S. Kim and N.-S. Cho, 433–439.

Experimental Estimation of the Load Distribution in Bearings by the Method of Caustics, 44(4), G.A., Papadopoulos, 440–443.

Experimental Evaluation of the Wyoming-modified Two-rail Shear Test Method for Composite Materials, 44(4), A.K. Hussian and D.F. Adams, 354–364.

Experimental Modal Analysis of a Synthetic Composite Femur, 44(1), J.F. Dias Rodridgues, H. Lopes, F.Q. de Melo and J.A. Simões, 29–32.

Experimental Studies on Thin-walled Grooved Tubes Under Axial Compression, 44(1), S.J. Hosseinipour and G.H. Daneshi, 101–108.

Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), B.D. Johnson, D.J. Beebe, D.J. Niedermaier, J.M. Bauer and W.C. Crone, 21–28.

Experimental Techniques For Testing Unstiffened Plates in Compression and Bending, 44(1), M.R. Bambach and K.J.R. Rasmussen, 91–96.

Experimental Verification of Drop/Impact Simulation for a Cellular Phone, 44(4), J.G. Kim and Y.K. Park, 375–380.

Failure Loads of Spot Weld Specimens Under Impact Opening and Shear Loading Conditions, 44(2), S.H. Lin, J. Pan, S. Wu and T. Tyan, 147–157.

Fatigue Cracking and Its Influence on Dynamic Response Characteristics of Spot Welded Specimens, 44(5), G. Wang and M.E. Barkey, 512–521.

Fatigue Damage Accumulation Around a Notch Using a Digital Image Measurement System, 44(3), F.V. Diaz, A.F. Armas, G.H. Kaufmann and G.E. Galizzi, 241–246.

Grid Method: Application to the Characterization of Cracks, 44(1), S. Avril, A. Vautrin and Y. Surrel, 37–43.

Impedance-based Non-destructive and Non-parametric Infrastructural Performance Evaluation, 44(1), K.K. Tseng, 109–112.

Improved Experimental Tracking Techniques for Validating DEM Simulations of Tumbling Mills, 44(6), I. Govender, A.T. McBride and M. S. Powell, 593–607.

Innovative Mechanical Device for the Post-tensioning of Glass Fiber Reinforced Polymer Bars for Masonry Type Retrofit Applications, 44(3), P. Yu, P.F. Silva and A. Nanni, 272–277.

Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(2), M.B. Prime, R.J. Sebring, J.M. Edwards, D.J. Hughes and P.J. Webster, 176–184.
Laser-assisted High-resolution Loading Dilatometer and Applications, 44(1), E. Aulbach, R. Zuo and J. Rödel, 71–75.
Loading and Unloading SHPB Pulse Shaping Techniques for Dynamic Hysteretic Loops, 44(6), B. Song and W.W. Chen, 622–627.
Local Time-Temperature-dependent Deformation of a Woven Composite, 44(4), P. Shrotriya and N.R. Sottos, 336–353.
Low Velocity Impact of Sandwich Composite Plates, 44(6) J. Gustin, M. Mahinfalah, G. Nakhaie Jazar and M. Rastgaar Aagaah, 574–583.
Luminescent Photoelastic Coatings, 44(4), J.P. Hubner, P.G. Ifju, L. Chen, K.S. Schanze, Y. Liu and W. El-Ratal, 416–424.
Mechanical Testing of Ultra-high Temperature Alloys, 44(2), R. Volkl and B. Fischer, 121–127.
Modal Parameter Prediction for Structures with Resistive Loaded Piezoelectric Devices, 44(1), A. Agneni and G. Coppotelli, 97–100.
More Comprehensive Method for Yield Locus Construction for Metallic Alloys and Composites, 44(1), C.J. Lissenden and X. Lei, A 10–20.
Multi-scanning Method for Fabricating Electron Moiré Grating, 44(6), Y.M. Xing, S. Kishimoto and N. Shinya, 562–566.
Murray Lecture: Breaking Paradigms, 44(6), C.P.Burger, 544–554.
Non-destructive Evaluation of the Interface Between Silicon Dies and Copper Leadframes in Integrated Circuit Packaging, 44(2), J. Abdul, N. Guo, H. Du, B.S. Wong and K.C. Chan, 113–120.
Optical Measurement of the Specimen Deformation at High Strain Rate, 44(3), P. Verleysen and J. Degrieck, 247–252.
Path Dependency in Thermoelastic Stress Analysis, 44(6) J.R. Estrada Estrada and E.A. Patterson, 567–573.
Photoelastic Model Measurement with Rotated Principal Axes by Scattered-light Photoelasticity, 44(5), T. Kihara, 455–460.
Photoelastic Stress Freezing Analysis of Total Shoulder Replacement Systems, 44(3), R.D. Peindl, M.E. Harrow, P.M. Connor, D.M. Banks and D.F. D'Alessandro, 228–234.
Plastic Surface Strain Mapping of Bent Sheets by Image Correlation, 44(5), W. Tong, 502–511.
Plotting Isoclinics for Hybrid Photoelasticity and Finite Element Analysis, 44(3), M. Ragulskis and L. Ragulskis, 235–240.
Pulsatile Flows in a Lateral Aneurysm Anchored on a Stented and Curved Parent Vessel, 44(3), T.-M. Liou and S.-N. Liou, 253–260.
Real-time Observation of Thermally Induced Warpage of Flip-chip Package Using Far-infrared Fizeau Interferometry, 44(6), K. Verma and B. Han, 628–633.
Seismic Behavior of Insulated Hollow-brick Cavity Walls Using Quasi-static Experimentation, 44(4), H.-N. Li, J.-W. Zhang and L. Liu, 396–406.
Some Aspects on the Zero-span Tensile Test, 44(4), R. Hagglund, P.A. Gradin and D. Tarakameh, 365–374.
Stress Intensity Factor Measurement of Cracks Using a Piezoelectric Element, 44(3), Y. Fujimoto, G. Liu, Y. Tanaka and E. Im, 320–325.
Stress Measurement of SS400 Steel Beam Using the Continuous Indentation Technique, 44(1), Y.-H. Lee, W.-J. Ji and D. Kwon, 55–61.
Stress-Strain Relationships for Spruce Wood: Influence of Strain Rate, Moisture Content and Loading Direction, 44(1), S. Widehammar, 44–48.
Surface Profiling Using Sequential Sampling and Inverse Methods. Part I: Mathematical Background, 44(5), G.S. Schajer and J.I. Gazzarri, 473–479.
Surface Profiling Using Sequential Sampling and Inverse Methods. Part II: Implementation and Experimental Results, 44(5), G. Schajer and J.I. Gazzarri, 480–486.
Temperature and Deformation Measurements in Transient Metal Cutting, 44(1), Y.K. Potdar and A.T. Zehnder, 1–9.
Thermoelastic Investigations for Fatigue Life Assessment, 44(5), R. Tomlinson and L. Marsavina, 487–494.
Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), C.-H. Chien, Y.-C. Chen, C.-C. Hsieh, Y.-D. Wu, Y.-T. Choiu and T. Chen, 214–220.
Uniaxial Material Damping Measurements Using a Fiber Optic Lattice: A Discussion of its Performance Envelope, 44(1), J. Aberg and B. Widell, 33–36.
Using Geometric Complexity to Enhance the Interfacial Strength of Heterogeneous Structures Fabricated in a Multi-stage, Multi-piece Molding Process, 44(3), H. Bruck, G. Fowler. S.K. Gupta and T.M. Valentine, 261–271.
Wave Propagation in Multi-wire Strands by Wavelet-based Laser Ultrasound, 44(4), P. Rizzo and F. Lanza di Scalea, 407–415.
Yield Behavior of Wood Under Combined Static Axial Force and Torque, 44(3), M. Yamasaki and Y. Sasaki, 221–227.
2004 Reviewers for Experimental Mechanics, 44(6), 634.

AUTHOR INDEX

Abdul, J.—Non-destructive Evaluation of the Interface Between Silicon Dies and Copper Leadframes in Integrated Circuit Packaging, 44(2), 113–120.
Aberg, J.—Uniaxial Material Damping Measurements Using a Fiber Optic Lattice: A Discussion of its Performance Envelope, 44(1), 33–36.
Adams, D.F.—Experimental Evaluation of the Wyoming-modified Two-rail Shear Test Method for Composite Materials, 44(4), 354–364.
Agneni, A.—Modal Parameter Prediction for Structures with Resistive Loaded Piezoelectric Devices, 44(1), 97–100.
Armas, A.F.—Fatigue Damage Accumulation Around a Notch Using a Digital Image Measurement System, 44(3), 241–246.
Atluri, S.N.—An Experimental-Numerical Evaluation of the T_{ε}^{*} Integral for a Three-dimensional Crack Front, 44(2), 207–213.
Aulbach, E.—Laser-assisted High-resolution Loading Dilatometer and Applications, 44(1), 71–75.
Avril, S.—Grid Method: Application to the Characterization of Cracks, 44(1), 37–43.
Bambach, M.R.—Experimental Techniques For Testing Unsttiffened Plates in Compression and Bending, 44(1), 91–96.
Banks, D.M.—Photoelastic Stress Freezing Analysis of Total Shoulder Replacement Systems, 44(3), 228–234.
Barkey, M.E.—Fatigue Cracking and Its Influence on Dynamic Response Characteristics of Spot Welded Specimens, 44(5), 512–521.
Barrau, J.J.—Combined Shear/Compression Structural Testing of Asymmetric Sandwich Structures, 44(5), 461–472.
Bauer, J.M.—Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), 21–28.
Beebe, D.J.—Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), 21–28.
Bruck, H.—Bending Actuation in Polyurethanes with a Symmetrically Graded Distribution of One-way Shape Memory Alloy Wires, 44(1), 62–70.
Bruck, H.—Using Geometric Complexity to Enhance the Interfacial Strength of Heterogeneous Structures Fabricated in a Multi-stage, Multi-piece Molding Process, 44(3), 261–271.
Burger, C.P., Murray Lecture: Breaking Paradigms, 44(6), 544–554.
Burton, W.—Effects of Measurement Techniques on the Experimental Characterization of Crack Tip Opening Angle-Δa Resistance Curves, 44(4), 425–432.
Castanie, B.—Combined Shear/Compression Structural Testing of Asymmetric Sandwich Structures, 44(5), 461–472.
Chan, K.C.—Non-destructive Evaluation of the Interface Between Silicon Dies and Copper Leadframes in Integrated Circuit Packaging, 44(2), 113–120.
Chen, W.—Dynamic Stress Equilibration in Split Hopkinson Pressure Bar Tests on Soft Materials, 44(3), 300–312.
Chen, L.—Luminescent Photoelastic Coatings, 44(4), 416–424.
Chen, T.—Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), 214–220.
Chen, W.W.—Dynamic Compressive Responses of Intact and Damaged Ceramics from a Single Split Hopkinson Pressure Bar Experiment, 44(3), 295–299.
Chen, W.W.—Loading and Unloading SHPB Pulse Shaping Techniques for Dynamic Hysteretic Loops, 44(6) 622–627.
Chen, Y.-C.—Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), 214–220.
Chiang, L.E., Dynamic Force-Penetration Curves in Rock by Matching Theoretical to Experimental Wave Propagation Response, 44(2), 167–175.
Chien, C.-H.—Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), 214–220.

Cho, N.-S.—Estimating Deflection of a Simple Beam Model Using Fiber Optic Bragg-grating Sensors, 44(4), 433–439.
Choiu, Y.-T.—Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), 214–220.
Coles, G.—Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), 49–54.
Connor, P.M.—Photoelastic Stress Freezing Analysis of Total Shoulder Replacement Systems, 44(3), 228–234.
Coppotelli, G.—Modal Parameter Prediction for Structures with Resistive Loaded Piezoelectric Devices, 44(1), 97–100.
Crone, W.C.—Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), 21–28.
D'Alessandro, D.F.—Photoelastic Stress Freezing Analysis of Total Shoulder Replacement Systems, 44(3), 228–234.
Daneshi, G.H.—Experimental Studies on Thin-Walled Grooved Tubes Under Axial Compression, 44(1), 101–108.
de Melo, F.Q.—Experimental Modal Analysis of a Synthetic Composite Femur, 44(1), 29–32.
Degrieck, Joris Optical Measurement of the Specimen Deformation at High Strain Rate, 44(3), 247–252.
Dias Rodridgues, J.F.—Experimental Modal Analysis of a Synthetic Composite Femur, 44(1), 29–32.
Dias, A.M.—An Empirical Methodology to Estimate a Local Yield Stress in Work-hardened Surface Layers, 44(1), 76–84.
Diaz, F.V.—Fatigue Damage Accumulation Around a Notch Using a Digital Image Measurement System, 44(3), 241–246.
Du, H.—Non-destructive Evaluation of the Interface Between Silicon Dies and Copper Leadframes in Integrated Circuit Packaging, 44(2), 113–120.
Edwards, J.M.—Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(2), 176–184.
Edwards, R.L.—Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), 49–54.
El-Ratal, W.—Luminescent Photoelastic Coatings, 44(4), 416–424.
Estrada Estrada, J.R.—Path Dependency in Thermoelastic Stress Analysis, 44(6), 567–573.
Fatemi, A.—A Novel Specimen for Investigating the Mechanical Behavior of Elastomers Under Multiaxial Loading Conditions, 44(2), 136–146.
Fischer, B.—Mechanical Testing of Ultra-high Temperature Alloys, 44(2), 121–127.
Fowler, G.—Using Geometric Complexity to Enhance the Interfacial Strength of Heterogeneous Structures Fabricated in a Multi-stage, Multi-piece Molding Process, 44(3), 261–271.
Fujimoto, Y.—Stress Intensity Factor Measurement of Cracks Using a Piezoelectric Element, 44(3), 320–325.
Galizzi, G.E.—Fatigue Damage Accumulation Around a Notch Using a Digital Image Measurement System, 44(3), 241–246.
Gan, C.—Analytical/Experimental Investigation of Energy Absorption in Grid-Stiffened Composite Structures Under Transverse Loading, 44(2), 185–194.
Garcia, D.—Advances in Light Microscope Stereo Vision, 44(3), 278–288.
Gazzarri, J.I.—Surface Profiling Using Sequential Sampling and Inverse Methods. Part I: Mathematical Background, 44(5), 473–479.
Gazzarri, J.I.—Surface Profiling Using Sequential Sampling and Inverse Methods. Part II: Implementation and Experimental Results, 44(5), 480–486.
Genovese, K.—A New Hybrid Technique for In-plane Characterization of Orthotropic Materials, 44(6), 584–592.
Gibson, R.F.—Analytical/Experimental Investigation of Energy Absorption in Grid-Stiffened Composite Structures Under Transverse Loading, 44(2), 185–194.
Goodwill, S.R.—Spin Generation for Oblique Impacts with a Tennis Racket, 44(2), 195–206.
Govender, I.—Improved Experimental Tracking Techniques for Validating DEM Simulations of Tumbling Mills, 44(6), 593–607.
Gradin, P.A.—Some Aspects on the Zero-span Tensile Test, 44(4), 365–374.
Guo, N.—Non-destructive Evaluation of the Interface Between Silicon Dies and Copper Leadframes in Integrated Circuit Packaging, 44(2), 113–120.
Gupta, S.K.—Using Geometric Complexity to Enhance the Interfacial Strength of Heterogeneous Structures Fabricated in a Multi-stage, Multi-piece Molding Process, 44(3), 261–271.
Gustin, J.—Low Velocity Impact of Sandwich Composite Plates, 44(6), 574–583.
Haake, S.J.—Spin Generation for Oblique Impacts with a Tennis Racket, 44(2), 195–206.
Hagglund, R.—Some Aspects on the Zero-span Tensile Test, 44(4), 365–374.
Han, B.—Real-time Observation of Thermally Induced Warpage of Flip-chip Package Using Far Infrared Fizeau Interferometry, 44(6), 628–633.
Harrow, M.E.—Photoelastic Stress Freezing Analysis of Total Shoulder Replacement Systems, 44(3), 228–234.
He, K.Y.—Determining Stress Intensity Factors in Orthotropic Composites From Far-Field Measured Temperatures, 44(6), 555–561.
Hong, J.-C.—Determination of the Optimal Gabor Wavelet Shape for the Best Time-frequency Localization Using the Entropy Concept, 44(4), 387–395.
Hosseinipour, S.J.—Experimental Studies on Thin-walled Grooved Tubes Under Axial Compression, 44(1), 101–108.
Hsieh, C.-C.—Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), 214–220.
Hubner, J.P.—Luminescent Photoelastic Coatings, 44(4), 416–424.
Hughes, D.J.—Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(2), 176–184.
Hummel, S.R.—A Procedure for Measuring Biaxial Viscoelastic Behavior of Thermoplastics, 44(4), 381–386.
Hussian, A.K.—Experimental Evaluation of the Wyoming-modified Two-rail Shear Test Method for Composite Materials, 44(4), 354–364.
Ifju, P.G.—Luminescent Photoelastic Coatings, 44(4), 416–424.
Iguchi, M.—Behavior of a Small Single Bubble Rising in a Rotating Flow Field, 44(5), 533–540.
Im, E.—Stress Intensity Factor Measurement of Cracks Using a Piezoelectric Element, 44(3), 320–325.
Jackson, J.H.—An Experimental-Numerical Evaluation of the T_{ε}^{*} Integral for a Three-dimensional Crack Front, 44(2), 207–213.
Jaouen, J.P.—Combined Shear/Compression Structural Testing of Asymmetric Sandwich Structures, 44(5), 461–472.
Ji, W.-J.—Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), 49–54.
Jia, D.—A Rigorous Assessment of the Benefits of Miniaturization in the Kolsky Bar System, 44(5), 445–454.
Johnson, B.D.—Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), 21–28.
Kaufmann, G.H.—Fatigue Damage Accumulation Around a Notch Using a Digital Image Measurement System, 44(3), 241–246.
Kihara, T.—Photoelastic Model Measurement with Rotated Principal Axes by Scattered-light Photoelasticity, 44(5), 455–460.
Kim, J.G.—Experimental Verification of Drop/Impact Simulation for a Cellular Phone, 44(4), 375–380.
Kim, N.-S.—Estimating Deflection of a Simple Beam Model Using Fiber Optic Bragg-grating Sensors, 44(4), 433–439.
Kim, Y.Y.—Determination of the Optimal Gabor Wavelet Shape for the Best Time-Frequency Localization Using the Entropy Concept, 44(4), 387–395.
Kimberley, J.—Dynamic Crack Kinking from a PMMA/Homalite Interface, 44(2), 158–166.
Kirugulige, M.S.—A Method for Measuring Mode I Crack Tip Constraint Under Static and Dynamic Loading Conditions, 44(5), 522–532.
Kishimoto, S.—Multi-Scanning Method for Fabricating Electron Moiré Grating, 44(6), 562–566.
Kobayashi, A.S.—An Experimental-Numerical Evaluation of the T_{ε}^{*} Integral for a Three-dimensional Crack Front, 44(2), 207–213.
Kornmeier, M.—An Empirical Methodology to Estimate a Local Yield Stress in Work-hardened Surface Layers, 44(1), 76–84.
Kuai, H.—Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part I: A Biologically Inspired Design, 44(6), 608–615.
Kuokkala, V.-T.—Effect of Strain Rate, Moisture and Temperature on the Deformation Behavior of Polymer Roll Covers, 44(3), 313–319.

Kwon, D.—Comparison of Tensile and Bulge Tests for Thin-Film Silicon Nitride, 44(1), 49–54.
Lamberti, L.—A New Hybrid Technique for In-Plane Characterization of Orthotropic Materials, 44(6), 584–592.
Lambros, J.—Dynamic Crack Kinking from a PMMA/Homalite Interface, 44(2), 158–166.
Lanza di Scalea, F.—Wave Propagation in Multi-wire Strands by Wavelet-based Laser Ultrasound, 44(4), 407–415.
Lease, K.—Effects of Measurement Techniques on the Experimental Characterization of Crack Tip Opening Angle-Δa Resistance Curves, 44(4), 425–432.
Lee, Y.-H.—Stress Measurement of SS400 Steel Beam Using the Continuous Indentation Technique, 44(1), 55–61.
Lei, X.—A More Comprehensive Method for Yield Locus Construction for Metallic Alloys and Composites, 44(1), 10–20.
Lesniak, J.—Design and Evaluation of the Poleidoscope: A Novel Digital Polariscope, 44(2), 128–135.
Li, H.-N.—Seismic Behavior of Insulated Hollow-brick Cavity Walls Using Quasi-static Experimentation, 44(4), 396–406.
Liechti, K.M.—A Piezoelectric Biaxial Loading Device for Interfacial Fracture Experiments, 44(5), 495–501.
Lin, S.H.—Failure Loads of Spot Weld Specimens Under Impact Opening and Shear Loading Conditions, 44(2), 147–157.
Liou, S.-N.—Pulsatile Flows in a Lateral Aneurysm Anchored on a Stented and Curved Parent Vessel, 44(3), 253–260.
Liou, T.-M.—Pulsatile Flows in a Lateral Aneurysm Anchored on a Stented and Curved Parent Vessel, 44(3), 253–260.
Lissenden, C.J.—A More Comprehensive Method for Yield Locus Construction for Metallic Alloys and Composites, 44(1), 10–20.
Liu, G.—Stress Intensity Factor Measurement of Cracks Using a Piezoelectric Element, 44(3), 320–325.
Liu, L.—Seismic Behavior of Insulated Hollow-brick Cavity Walls Using Quasi-static Experimentation, 44(4), 396–406.
Liu, Q.—Crushability Maps for Structural Polymeric Foams in Uniaxial Loading Under Rigid Confinement, 44(3), 289–294.
Liu, Y.—Luminescent Photoelastic Coatings, 44(4), 416–424.
Lopes, H.—Experimental Modal Analysis of a Synthetic Composite Femur, 44(1), 29–32.
Luo, H.—Dynamic Compressive Responses of Intact and Damaged Ceramics from a Single Split Hopkinson Pressure Bar Experiment, 44(3), 295–299.
Mahinfalah, M.—Low Velocity Impact of Sandwich Composite Plates, 44(6), 574–583.
Mahmoud, S.—Effects of Measurement Techniques on the Experimental Characterization of Crack Tip Opening Angle-Δa Resistance Curves, 44(4), 425–432.
Maleski, M.J.—A Method for Measuring Mode I Crack Tip Constraint Under Static and Dynamic Loading Conditions, 44(5), 522–532.
Mars, W.V.—A Novel Specimen for Investigating the Mechanical Behavior of Elastomers Under Multiaxial Loading Conditions, 44(2), 136–146.
Marsavina, L.—Thermoelastic Investigations for Fatigue Life Assessment, 44(5), 487–494.
McBride, A.T.—Improved Experimental Tracking Techniques for Validating DEM Simulations of Tumbling Mills, 44(6), 593–607.
Mello, A.W.—A Piezoelectric Biaxial Loading Device for Interfacial Fracture Experiments, 44(5), 495–501.
Moore, III, C.L.—Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), 49–54.
Nakhaie Jazar, G.—Low Velocity Impact of Sandwich Composite Plates, 44(6), 574–583.
Nanni, A.—Innovative Mechanical Device for the Post-tensioning of Glass Fiber Reinforced Polymer Bars for Masonry Type Retrofit Applications, 44(3), 272–277.
Newaz, G.M.—Analytical/Experimental Investigation of Energy Absorption in Grid-Stiffened Composite Structures Under Transverse Loading, 44(2), 185–194.
Nied, H.F.—A Procedure for Measuring Biaxial Viscoelastic Behavior of Thermoplastics, 44(4), 381–386.
Niedermaier, D.J.—Experimental Techniques for Mechanical Characterization of Hydrogels at the Microscale, 44(1), 21–28.
Nobre, J.P.—An Empirical Methodology to Estimate a Local Yield Stress in Work-hardened Surface Layers, 44(1), 76–84.
Pan, J.—Failure Loads of Spot Weld Specimens Under Impact Opening and Shear Loading Conditions, 44(2), 147–157.
Papadopoulos, G.A., Experimental Estimation of the Load Distribution in Bearings by the Method of Caustics, 44(4), 440–443.
Pappalettere, C.—A New Hybrid Technique for In-plane Characterization of Orthotropic Materials, 44(6), 584–592.
Park, Y.K.—Experimental Verification of Drop/Impact Simulation for a Cellular Phone, 44(4), 375–380.
Patterson, E.A.—Design and Evaluation of the Poleidoscope: A Novel Digital Polariscope, 44(2), 128–135.
Patterson, E.A.—Path Dependency in Thermoelastic Stress Analysis, 44(6), 567–573.
Peindl, R.D.—Photoelastic Stress Freezing Analysis of Total Shoulder Replacement Systems, 44(3), 228–234.
Potdar, Y.K.—Temperature and Deformation Measurements in Transient Metal Cutting, 44(1), 1–9.
Powell, M.S.—Improved Experimental Tracking Techniques for Validating DEM Simulations of Tumbling Mills, 44(6), 593–607.
Prime, M.B.—Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(2), 176–184.
Prime, M.B.—Erratum to Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(5), 541–541.
Ragulskis, L.—Plotting Isoclinics for Hybrid Photoelasticity and Finite Element Analysis, 44(3), 235–240.
Ragulskis, M.—Plotting Isoclinics for Hybrid Photoelasticity and Finite Element Analysis, 44(3), 235–240.
Ramesh, K.T.—A Rigorous Assessment of the Benefits of Miniaturization in the Kolsky Bar System, 44(5), 445–454.
Rasmussen, K.J.R.—Experimental Techniques For Testing Unstiffened Plates in Compression and Bending, 44(1), 91–96.
Rastgaar Aagaah, M.—Low Velocity Impact of Sandwich Composite Plates, 44(6), 574–583.
Rivallant, S.—Combined Shear/Compression Structural Testing of Asymmetric Sandwich Structures, 44(5), 461–472.
Rizzo, P.—Wave Propagation in Multi-wire Strands by Wavelet-based Laser Ultrasound, 44(4), 407–415.
Rödel, J.—Laser-assisted High-resolution Loading Dilatometer and Applications, 44(1), 71–75.
Rowlands, R.E.—Determining Stress Intensity Factors in Orthotropic Composites From Far-Field Measured Temperatures, 44(6), 555–561.
Sasaki, Y.—Yield Behavior of Wood Under Combined Static Axial Force and Torque, 44(3), 221–227.
Schajer, G.—Surface Profiling Using Sequential Sampling and Inverse Methods. Part II: Implementation and Experimental Results, 44(5), 480–486.
Schajer, G.S.—Surface Profiling Using Sequential Sampling and Inverse Methods. Part I: Mathematical Background, 44(5), 473–479.
Schanze, K.S.—Luminescent Photoelastic Coatings, 44(4), 416–424.
Schreier, Hubert Advances in Light Microscope Stereo Vision, 44(3), 278–288.
Sebring, R.J.—Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(2), 176–184.
Sengupta, S.—Dissimilar Material Joints With and Without Free-edge Stress Singularities, Part I: A Biologically Inspired Design, 44(6), 608–615.
Sengupta, S.—Dissimilar Material Joints With and Without Free-edge Stress Singularities, Part II: An Integrated Numerical Analysis, 44(6): 616–621.
Sgalla, M.—A Device for Measuring the Velocity of Ultrasonic Waves: An Application to Stress Analysis, 44(1), 85–90.
Sharpe, Jr., W.N.—Comparison of Tensile and Bulge Tests for Thin-film Silicon Nitride, 44(1), 49–54.
Shinya, N.—Multi-scanning Method for Fabricating Electron Moiré Grating, 44(6), 562–566.
Shrotriya, P.—Local Time-Temperature-dependent Deformation of a Woven Composite, 44(4), 336–353.
Silva, P.F.—Innovative Mechanical Device for the Post-tensioning of Glass Fiber Reinforced Polymer Bars for Masonry Type Retrofit Applications, 44(3), 272–277.
Simões,J.A.—Experimental Modal Analysis of a Synthetic Composite Femur, 44(1), 29–32.
Song, B.—Dynamic Stress Equilibration in Split Hopkinson Pressure Bar Tests on Soft Materials, 44(3), 300–312.

Song, B.—Loading and Unloading SHPB Pulse Shaping Techniques for Dynamic Hysteretic Loops, 44(6), 622–627.
Sottos, N.R.—Local Time-Temperature-dependent Deformation of a Woven Composite, 44(4), 336–353.
Sottos, N.R.—Editorial, 44(6), 543.
Subhash, G.—Crushability Maps for Structural Polymeric Foams in Uniaxial Loading Under Rigid Confinement, 44(3), 289–294.
Surrel, Y.—Grid Method: Application to the Characterization of Cracks, 44(1), 37–43.
Sutton, M.A.—Advances in Light Microscope Stereo Vision, 44(3), 278–288.
Tanaka, Y.—Stress Intensity Factor Measurement of Cracks Using a Piezoelectric Element, 44(3), 320–325.
Tarakameh, D.—Some Aspects on the Zero-span Tensile Test, 44(4), 365–374.
Tippur, H.V.—A Method for Measuring Mode I Crack Tip Constraint Under Static and Dynamic Loading Conditions, 44(5), 522–532.
Tomlinson, R.—Thermoelastic Investigations for Fatigue Life Assessment, 44(5), 487–494.
Tong, W.—Plastic Surface Strain Mapping of Bent Sheets by Image Correlation, 44(5), 502–511.
Tseng, K.K., Impedance-based Non-destructive and Non-parametric Infrastructural Performance Evaluation, 44(1), 109–112.
Tyan, T.—Failure Loads of Spot Weld Specimens Under Impact Opening and Shear Loading Conditions, 44(2), 147–157.
Uemura, T.—Behavior of a Small Single Bubble Rising in a Rotating Flow Field, 44(5), 533–540.
Valentine, T.M.—Comparison of Tensile and Bulge Tests for Thin-Film Silicon Nitride, 44(1), 49–54.
Valentine, T.M.—Using Geometric Complexity to Enhance the Interfacial Strength of Heterogeneous Structures Fabricated in a Multistage, Multi-piece Molding Process, 44(3), 261–271.
Vangi, D.—A Device for Measuring the Velocity of Ultrasonic Waves: An Application to Stress Analysis, 44(1), 85–90.
Vautrin, A.—Grid Method: Application to the Characterization of Cracks, 44(1), 37–43.
Vavrik, D.—Crack Instability in Ductile Materials Analyzed by the Method of Interpolated Ellipses, 44(4), 327–335.
Verleysen, Patricia Optical Measurement of the Specimen Deformation at High Strain Rate, 44(3), 247–252.
Verma, K.—Real-time Observation of Thermally Induced Warpage of Flip-chip Package Using Far Infrared Fizeau Interferometry, 44(6), 628–633.
Volkl, R.—Mechanical Testing of Ultra-high Temperature Alloys, 44(2), 121–127.
Vuoristo, T.—Effect of Strain Rate, Moisture and Temperature on the Deformation Behavior of Polymer Roll Covers, 44(3), 313–319.
Wang, G.—Fatigue Cracking and Its Influence on Dynamic Response Characteristics of Spot Welded Specimens, 44(5), 512–521.
Webster, P.J.—Laser Surface-contouring and Spline Data-smoothing for Residual Stress Measurement, 44(2), 176–184.
Widehammar, S., Stress-Strain Relationships for Spruce Wood: Influence of Strain Rate, Moisture Content and Loading Direction, 44(1), 44–48.
Widell, B.—Uniaxial Material Damping Measurements Using a Fiber Optic Lattice: A Discussion of its Performance Envelope, 44(1), 33–36.
Wong, B.S.—Non-destructive Evaluation of the Interface Between Silicon Dies and Copper Leadframes in Integrated Circuit Packaging, 44(2), 113–120.
Wu, S.—Failure Loads of Spot Weld Specimens Under Impact Opening and Shear Loading Conditions, 44(2), 147–157.
Wu, Y.-D.—Thermomechanical Behavior of Underfill/Solder Mask/Substrate Interface Under Thermal Cycling, 44(2), 214–220.
Xing, Y.M.—Multi-Scanning Method for Fabricating Electron Moiré Grating, 44(6), 562–566.
Xu, L.R.—Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part I: A Biologically Inspired Design, 44(6), 608–615.
Xu, L.R.—Dissimilar Material Joints With and Without Free-Edge Stress Singularities, Part II: An Integrated Numerical Analysis, 44(6), 616–621.
Yamaguchi, T.—Behavior of a Small Single Bubble Rising in a Rotating Flow Field, 44(5), 533–540.
Yamasaki, M.—Yield Behavior of Wood Under Combined Static Axial Force and Torque, 44(3), 221–227.
Yu, P.—Innovative Mechanical Device for the Post-tensioning of Glass Fiber Reinforced Polymer Bars for Masonry Type Retrofit Applications, 44(3), 272–277.
Zehnder, A.T.—Temperature and Deformation Measurements in Transient Metal Cutting, 44(1), 1–9.
Zemankova, J.—Crack Instability in Ductile Materials Analyzed by the Method of Interpolated Ellipses, 44(4), 327–335.
Zhang, J.-W.—Seismic Behavior of Insulated Hollow-brick Cavity Walls Using Quasi-static Experimentation, 44(4), 396–406.
Zhang, S.J.—Design and Evaluation of the Poleidoscope: A Novel Digital Polariscope, 44(2), 128–135.
Zuo, R.—Laser-assisted High-resolution Loading Dilatometer and Applications, 44(1), 71–75.
2004 Reviewers for Experimental Mechanics, 44(6), 634.